

Operating Systems Security III

CS 1660: Introduction to Computer Systems
Security

So setuid/setgid is dangerous...

setuid/setgid is dangerous...

In modern times: only for programs that really need it

- System programs that changing passwords/users, legacy programs
 - Don't do this yourself!
- Very very bad idea for shell scripts

What else can we do?

When do we need this?

In the shell: su, sudo

- Run as another user (if you have permissions)

```
user@shell:~$ su -c "command" other user
```

- Run commands as root (or another user) based on system config file (/etc/sudoers)

- Can restrict to specific commands, environment,

```
user@shell:~$ sudo whoami  
root
```

```
/etc/sudoers:  
%wheel ALL=(ALL) NOPASSWD: ALL  
  
. . .
```

From man page on /etc/sudoers: (aka sudoers(5))

```
ALL                CDROM = NOPASSWD: /sbin/umount /CDROM,\  
                  /sbin/mount -o nosuid,nodev /dev/cd0a /CDROM
```

Any user may mount or unmount a CD-ROM on the machines in the CDROM Host_Alias (orion, perseus, hercules) without entering a password.

sudo has a LOT of features, see
man sudoers for details!

What ELSE could we do?

Separation of processes

- System service runs as privileged user
- Client program run by unprivileged users
- Some API for how these programs communicate
 - Local network connection
 - Unix socket
 - dbus or other IPC mechanism
 - ...

One way: Separation of processes

- System service runs as privileged user
- Client program run by **unprivileged** users
- Some API for how these programs communicate
 - Local network connection
 - Unix socket
 - dbus or other IPC mechanism
 - ...

=> Better control over *how* privileged code runs

=> Interface between privileged/unprivileged defined more clearly

Example: docker

Other ways?

- What does it mean for the user to be "unprivileged"?
- What does it mean for code run by a user to be "unprivileged"?
- What do we want that code to be able to do?
=> How much do we trust the user? The code?

One way: Isolation within OS

Linux namespaces (+ related features): give processes/users separate views of userspace components

One way: Isolation within OS

Linux namespaces (+ related features): give processes/users separate views of userspace components

- chroot (separate filesystem trees)
- Processes trees
- UIDs/GIDs
- cgroups (Resource limits/quotas)
- Network connections
- Time
- ...

Not a security feature *per se*, but can help...

Example: chroot (1980s)

- "Change root"
- Run command with separate root directory
- All child processes inherit this root directory
- Implications?

If you need to do this in practice: look up "schroot"

Containers (ie, Docker) [ON LINUX]

Automated way to run applications

- Leverages lots of Linux namespaces at once
- Super great for deploying software!!

Example: course container

What do we notice?

- Separate filesystem
- Separate UIDs/GIDs
 - Can be root in the container => does it matter?
- Separate network interfaces, etc.
- When running the container, we decide what resources are shared with the host (files, network, etc)

Isolation mediated by Docker, OS kernel

What does this mean?

- Easy to "punch holes" depending on configuration
 - Shared directories, "privileged containers", ...
- Namespaces are growing all the time
- Docker has lots of permissions levels for what privileges containers can use

A lot of "knobs"...

- What if the configuration is incorrect?
- What if the kernel has a bug?

Another way: Virtual Machines (VMs)

Isolated way to run an entire system (hardware, kernel, ...)

Another way: Virtual Machines (VMs)

Isolated way to run an entire system (hardware, kernel, ...)

- A whole OS could run as a program
- Modern systems: hardware support for isolating memory, page tables, etc. and preserving performance
 - Curious? Take CS1670.
- Virtual hardware/drivers to interact with host

=> "Stronger" isolation, possibly more overhead for configuration/performance vs. containers

Example: A VM

So where should we run our untrusted code?

- Functionality: What privileges should the code (or the user) have?
- Threat model: What are the attacker's capabilities?

Docker on Windows, Mac?

Windows/Mac don't have Linux namespaces...

Malware

CS 1660: Introduction to Computer
Systems Security

Viruses, Worms, Trojans, Rootkits

- **Malware :**
 - A software that is specifically designed to disrupt, damage, or gain unauthorized access to a computer system
 - It can be classified into several categories, depending on propagation and concealment
- Propagation
 - **Virus:** human-assisted propagation (e.g., open email attachment)
 - **Worm:** automatic propagation without human assistance
- Concealment
 - **Rootkit:** modifies operating system to hide its existence
 - **Trojan:** provides desirable functionality but hides malicious operation (i.e. *payload*)
- Various types of payloads, ranging from annoyance to crime, breaks of Confidentiality, Integrity, and Availability

A Brief History of Malware

Early History


- 1972: sci-fi novel “When HARLIE Was One” features self-reproducing computer program called VIRUS
- 1982: high-school student Rich Skrenta wrote first virus released in the wild, Elk Cloner, a boot sector virus
- 1984: first academic use of “virus” by PhD student **Fred Cohen**, who credits advisor Len Adleman
- 1986: (c)Brain, by Basit and Amjood Farooq Alvi, credited with being first virus to infect PCs
- 1987: CHRISTMA EXEC targeting IBM VM/CMS systems was first email worm
- 1988: first internet worm, **Morris Worm** by Cornell student Robert Tappan Morris



Source: Wired, <https://www.wired.com/2011/07/0726first-computer-fraud-indictment/>

Previous Decade 2000-2009

- New malware threats have grown from 20K to 3M in the period 2002-2009
- Most of the growth has been from 2006 to 2009
- Growth in professional cybercrime and online fraud led to demand for professionally developed malware
- New malware often a custom-designed variation of known one
- Most notable: MELISSA, ILOVEYOU, CODE RED, NIMDA, etc.
- Let see the modern malwares...



Source: Symantec Internet Security Threat Report

Malware Vectors, Propagation and Concealment

Some Malware Vectors

- **Compromised Legitimate Websites**
 - Theft of credentials
 - Malicious downloads Mobile Apps
 - Exfiltration of personal information
 - Invasive ads
- **IoT Devices**
 - Rarely patched
 - Provide access to private networks of homes and offices
- **Email through phishing or spamming/spoofing**
 - Includes malicious links or attachments
 - Tricks users to send money or reveal passwords with social engineering
 - Mass distribution or targeted to specific users
 - About 50% of email volume is malware-related

A malware vector: Phishing

- Attempt to fraudulently acquire sensitive information
 - Passwords, credit card numbers, etc.
- Usually copies the HTML of a website and tries to pass off as a sub-site of that page.
- Phishers create a page or e-mail (**spam**) that appears to be from another source
- Usually relies on the user not exploring the page in depth
- Famous phishing attempts are PayPal and eBay scams
- Examples on www.phishtank.com, openphish.com

From: PayPal Security Department [service@paypal.com]
Subject: [SPAM:99%] Your PayPal Account



Security Center Advisory!

We recently noticed one or more attempts to log in to your PayPal account from a foreign IP address and we have reasons to believe that your account was hijacked by a third party without your authorization. If you recently accessed your account while traveling, the unusual log in attempts may have been initiated by you.

If you are the rightful holder of the account you must **click the link below** and then complete all steps from the following page as we try to verify your identity.

[Click here to verify your account](#)

http://211.248.156.177/.PayPal/cgi-bin/websecrmd_login.php

If you choose to ignore our request, you leave us no choice but to temporarily suspend your account.

Thank you for using PayPal!

Please do not reply to this e-mail. Mail sent to this address cannot be answered. For assistance, [log in](#) to your PayPal account and choose the "Help" link in the footer of any page.

To receive email notifications in plain text instead of HTML, update your preferences [here](#).

PayPal Email ID PP697

Protect Your Account Info

Make sure you never provide your password to fraudulent persons.

PayPal automatically encrypts your confidential information using the Secure Sockets Layer protocol (SSL) with an encryption key length of 128-bits (the highest level commercially available).

PayPal will never ask you to enter your password in an email.

For more information on protecting yourself from fraud, please review our Security Tips at <http://www.paypal.com/securitytips>

Protect Your Password

You should never give your PayPal password to anyone, including PayPal employees.

My Apple ID

Sign in to manage your

Sign in.

Extended Validation Certificate

My Apple ID

Verify your email address.

Please verify the email address,
associated with your Apple ID

Sign in to Verify your email address.


Apple ID

[Forgot your Apple ID?](#)

Password

Extended Validation Certificate: Firefox


- Instant Website ID
 - A color-coded system makes it easy to check on suspicious sites and avoid Web forgeries.
- Anti-Phishing & Anti-Malware
 - Firefox protects you from trojan horses and spyware, and warns you away from fraudulent sites.



“why would anyone give their personal data to a phisher?”

- **Spear Phishing**
 - Phishing attempts directed at specific individuals or companies
 - Attackers may gather personal information about their target to increase their probability of success
- **Whaling**
 - Attacks directed specifically at senior executives and other high profile targets within businesses,
- These attacks are very difficult to understand and usually use email system

E-mail Transport



Sender

Recipient

- **MUA:** mail user agent, *aka* mail client
- **MTA:** mail transport agent, *aka* mail server

SMTP

- Simple Mail Transfer Protocol
 - Client connects to server on TCP port 25
 - RFC 821 (1982) – 2821 (2001)
 - Client sends commands to server
 - Server acks or notifies of error
- Security issues
 - Sender not authenticated
 - Message and headers transmitted in plain text
 - Message and header integrity not protected
 - Spoofing and Spamming trivial to accomplish

- Example SMTP session

HELO mail.cs.brown.edu

MAIL FROM:<joe_biden@whitehouse.gov>

RCPT TO:<bernardo_palazzi@brown.edu>

DATA

Subject: Executive order

Date: Tue, March 21, 2023


You are hereby ordered to grade all the students of CS 166 class with A.

The President of the United States

•


Sender ID and Sender Policy Framework (SPF)

- Store DNS records about servers authorized to send mail for a given domain
- Look up domain in From header to find IP address of authorized mail server



DomainKeys Identified Mail (DKIM)

- Sender's mail server signs email to authenticate domain
- Public key of server available in DNS record
- To be used in conjunction with other spam filtering methods



DomainKey-Signature: a=rsa-sha1; s=mail;
d=example.net; c=simple; q=dns;
b=Fg...5J

Authentication-Results: example.net
from=bob@example.net;
domainkeys=pass;

DMARC

- Domain-based Message Authentication, Reporting & Conformance
- Allows you to get reports back on the effectiveness of your SPF and DKIM investments
- Validates that the “From” header is the same as the domains validated by SPF and DKIM
- Provides clear instructions to the receiving server on what to do with emails that fail SPF or DKIM
- Google message header validator:
 - <https://toolbox.googleapps.com/apps/messageheader/>



Author Composes
& Sends Email

Sending Mail Server
Inserts DKIM Header

Email Sent to
Receiver

SENDER RECEIVER

IP Blocklists,
Reputation,
Rate Limits,
etc.

Standard
Validation
Tests

Validate and Apply Sender DMARC Policy

Retrieve
Verified DKIM
Domains

Retrieve
"Envelope From"
via SPF

Apply Appropriate
DMARC Policy

Anti-Spam
Filters, etc.

Standard
Processing

Passed

Quarantine



none


Update the periodic
Aggregate Report
to be sent to Sender

Failure Report sent to Sender

DMARC.org

Infection Types

- Overwriting
 - Destroys original code
- Pre-pending
 - Keeps original code, possibly compressed
- Infection of libraries
 - Allows virus to be memory resident
 - E.g., kernel32.dll
- Macro viruses
 - Infects MS Office documents
 - Often installs in main document template



Worm Development

- Identify vulnerability still unpatched
- Write code for
 - Exploit of vulnerability
 - Generation of target list
 - Random hosts on the internet
 - Hosts on LAN
 - Divide-and-conquer
 - Installation and execution of payload
 - Querying/reporting if a host is infected
- Initial deployment on botnet
- Worm template
 - Generate target list
 - For each host on target list
 - Check if infected
 - Check if vulnerable
 - Infect
 - Recur
- Distributed graph search algorithm
 - Forward edges: infection
 - Back edges: already infected or not vulnerable

Concealment

- **Encrypted virus**
 - Decryption engine + encrypted body
 - Randomly generate encryption key
 - Detection looks for decryption engine
- **Polymorphic virus**
 - Encrypted virus with random variations of the decryption engine (e.g., padding code)
 - Detection using CPU emulator
- **Metamorphic virus**
 - Different virus bodies
 - Approaches include code permutation and instruction replacement
 - Challenging to detect

Rootkits

- A rootkit modifies the operating system to hide its existence
 - E.g., modifies file system exploration utilities (e.g., ls, cd, ...)
 - Hard to detect using software that relies on the OS itself
- RootkitRevealer for Windows
 - By Bryce Cogswell and Mark Russinovich (Sysinternals)
 - Two scans of file system
 - High-level scan using the Windows API
 - Raw scan using disk access methods
 - Discrepancy reveals presence of rootkit
 - Could be defeated by rootkit that intercepts and modifies results of raw scan operations

What We Have Learned

- Types of malware
- Historical evolution of malware
- Modeling malware propagation:
 - phishing and email spoofing
- Concealment techniques

Malwares for a Cyberwar

Cyberweapons

- Starting from 2010 several viruses acted as a sort of weapons in international relationships
- Usually is not confirmed by governments
- Most famous:
 - 2010 Stuxnet
 - 2012 Flame
 - 2020 Orion Solarwinds ???

Software Sabotage

How Stuxnet disrupted Iran's uranium enrichment program



1 The malicious computer worm probably entered the computer system – which is normally cut off from the outside world – at the uranium enrichment facility in Natanz via a removable USB memory stick.

2 The virus is controlled from servers in Denmark and Malaysia with the help of two Internet addresses, both registered to false names. The virus infects some 100,000 computers around the world.


3 Stuxnet spreads through the system until it finds computers running the Siemens control software. Step 7, which is responsible for regulating the rotational speed of the centrifuges.

4 The computer worm varies the rotational speed of the centrifuges. This can destroy the centrifuges and impair uranium enrichment.

Iranian centrifuges for uranium enrichment



5 The Stuxnet attacks start in June 2009. From this point on, the number of inoperative centrifuges increases sharply.



Source: IAEA, ISIS, FAS, World Nuclear Association, FT research

Stuxnet: Command & Control (C&C)

- Once a system was infected Stuxnet checked two fake web domains:
 - mypremierfutbol.com
 - todaysfutbol.com
 - Registered with two fake names and credit cards
 - Servers pointed to Denmark and Malaysia
- Virus sent encrypted information about the infected target
 - Windows version
 - Internal IP address
 - Targeted Siemens sw installed
- If target does not have Siemens sw installed
 - The payload does not start
 - The worm spreads to other target

NEW "FLAME" CYBER WEAPON

Article in 2012

Kaspersky Lab, one of the world's largest makers of anti-virus software, discovered a new malware codenamed "Worm.Win32.Flame," or simply "Flame," the most complex piece of malicious software yet found.

COMPLEXITY

Comprising almost 20 MB in size and some 20 modules of code when fully deployed, Flame is one of the biggest examples of malicious software ever discovered

BREADTH

Virus can record sounds, access Bluetooth communications, capture screenshot images and log internet messaging conversations

NETWORK

The creators of the virus used a network of some 80 servers across Asia, Europe and North America to remotely control infected machines



VICTIMS

Researchers estimate that altogether between 1,000 and 5,000 machines are infected worldwide, with the larger number of infected computers found in the Middle East

Possible initial infection



Affected hardware



PERPETRATOR

Kaspersky researchers declined to say which nation or nations they believe are behind Flame

Flame details

- >80 Domains for C&C
- **Innovative attack Vector:** Flame used a rogue Microsoft signed update based on a md5 hash collision
 - More to come with Orion Solarwinds attack...
- Flame targets different office files (e.g. word, excel) and also AutoCAD
 - Usually the malware extracted 1 KB of text from each file and transmitted it back to the C&C, where there was probably a supercomputer to elaborate which file could be interesting
- Patient zero?
 - Difficult to establish, the first infection uncovered was dated December 2007 in Europe, but Flame could potentially alter the timestamp to prevent researchers from dating the work

Data breach and finance

The Equifax Breach

- Equifax is a leading credit reporting agency
- Keeps personal information and credit history for virtually every American
- In the summer of 2017, sensitive personal information about 148 million people was stolen
 - Name
 - Date of birth
 - Address
 - Social security number
- Attackers exploited vulnerability in popular web server software
 - Apache Struts code for Java web applications was vulnerable to remote code execution
 - Attacker only needed a browser
- Vulnerability had existed for years
 - Variants reported in March and September 2017
- First patch available in March 2017

The Equifax Breach One Year Later

- The CEO resigned shortly after the revelation of the breach
 - Forfeited a \$3M bonus
 - Kept \$18M in pension benefits
- Other executives also resigned
- The stock shed about 1/3 of its value in the following month but recouped most of the loss after one year
- No significant action taken for consumer reparation and no substantive regulatory changes since the breach
- US senators Elizabeth Warren and Mark Warner introduced a bill to hold credit agencies accountable for data theft



Source: Sentieo, Inc.

<https://qz.com/1383810/equifax-data-breach-one-year-later-no-punishment-for-the-company/>
<http://fortune.com/2018/09/07/equifax-data-breach-one-year-anniversary/>

Break!!!!!!

60

60

60

60

60

Class is starting now!

Impossibility of Malware Detection

Undecidability

- Undecidable problem:
A yes/no problem for which there exists no algorithm that always returns an answer.
- Halting Problem:
Will this arbitrary program eventually return?
Alan Turing (1936)
- We can prove that problems are undecidable.

Proof of Undecidability of the Halting Problem

- Suppose algorithm *halts*(P) can decide if any program P halts.
- We can show by contradiction that no such algorithm exists.

```
def prog():  
    if halts(prog):  
        loop_forever()
```

- *halts* returns True:
prog loops forever
- *halts* returns False:
prog terminates

Contradiction: no algorithm *halts* can exist.

Virus Detection is Undecidable

- Theoretical result by Fred Cohen (1987)
- Virus abstractly modeled as program that eventually executes **infect**
- Code for **infect** may be generated at runtime
- Proof by contradiction similar to that of the halting problem

- Suppose program **isVirus**(P) determines whether program P is a virus

```
def prog():  
    if (not isVirus(prog)):  
        infect
```

Running **isVirus** on the code of **prog** achieves a contradiction

Virus Detection is Undecidable

- Another example
- Define program `prog()` as:

```
{  
    foo();    // harmless code  
    infect  
}
```

- Let's run `isVirus(prog)`
 - If `foo()` can return, `isVirus` should return True
 - If `foo()` never returns (eg infinite loop), then `isVirus` should return False because `infect` will never execute
- `isVirus` must determine whether `foo()` can ever halt. This is the **halting problem**, which is known to be undecidable.

Clicker Question

Which of the following statements summarizes what it means to say that virus detection is undecidable?

- A. Virus detection is theoretically possible but exceedingly difficult to program
- B. Assuming the existence of a virus detection program leads to a logical contradiction
- C. Virus detection is a problem whose solution requires an exponential time algorithm
- D. None of the above

Clicker Question - Answer

Which of the following statements summarizes what it means to say that virus detection is undecidable?

- A. Virus detection is theoretically possible but exceedingly difficult to program
- B. Assuming the existence of a virus detection program leads to a logical contradiction
- C. Virus detection is a problem whose solution requires an exponential time algorithm
- D. None of the above

Other Undecidable Detection Problems

- Detection of a virus
 - by its appearance
 - by its behavior
- Detection of a triggering mechanism
 - by its appearance
 - by its behavior
- Detection of a virus detector
 - by its appearance
 - by its behavior
- Detection of an evolution of
 - a known virus
 - a known triggering mechanism
 - a virus detector

Malware Detection

Detection Works Where Prevention Fails

- Detection is the act of noticing or discovering something

Detection by its appearance

- Detects specific malicious **signatures**
- Often uses fast pattern matching techniques
- Problems?
 - False negative
Signature Evasion

Detection by its behavior

- Detects **anomalies** on a normal system/network activity
- Often uses machine learning
- Problems?
 - False positive
Legitimate behavior could be not standard

High Cost of Errors

- False Positives FP require expensive analysis time
- False Negatives can be catastrophic
- Examples?
 - **Airport Security:** FP is when ordinary items such as keys or coins get mistaken for weapons (machine goes "beep")
 - **Quality Control:** FP is when a good quality item gets rejected, and a FN is when a poor quality item gets accepted
 - **Presumption of innocence:** "It is better that ten guilty persons FN escape than that one innocent suffer FP"
 - **Antivirus software:** a FP is when a normal file is thought to be a virus

Signatures

- Scan compares the analyzed object with a database of signatures
- A **signature** is a virus fingerprint
 - E.g., a string with a sequence of instructions specific for each virus
 - **Different from a digital signature**
- A file is infected if there is a signature inside its code
 - Fast **pattern matching** techniques to search for signatures
- All the signatures together create the malware database that usually is proprietary

Heuristic Analysis

- Useful to identify new and “zero day” malware
- Code analysis
 - Based on the instructions, the antivirus can determine whether or not the program is malicious, i.e., program contains instruction to delete system files,
- Execution emulation (sandbox)
 - Run code in isolated emulation environment
 - Monitor actions that target file takes
 - If the actions are harmful, mark as virus
- Heuristic methods can trigger false alarms

Online vs Offline Anti Virus Software

Online

- Free browser plug-in
- Authentication through third party certificate (i.e. VeriSign)
- No shielding
- Software and signatures update at each scan
- Poorly configurable
- Scan needs internet connection
- Report collected by the company that offers the service

Offline

- Paid annual subscription
- Installed on the OS
- Software distributed securely by the vendor online or a retailer
- System shielding
- Scheduled software and signatures updates
- Easily configurable
- Scan without internet connection
- Report collected locally and may be sent to vendor

Anti Malware Software Today

- In addition to signature-based scanning, behavior-based detection and sandboxing, anti malware software may also rely on reputation-based systems with information about current malware in the wild
- Symantec's STAR malware protection technologies rely on the following:
 - **File-Based Protection** continues to play a major protection role due to new innovations in static file heuristics.
 - **Network-Based Protection** can detect when both known and unknown vulnerabilities are used to enter a user's system.
 - **Behavior-Based Protection** looks at the dynamic behavior of malicious activity rather than static characteristics.
 - **Reputation-Based Protection** examines the meta information of a file – its age, origin, how it travels, where it exists, etc.
 - **Remediation** is a set of technologies that can help clean up an infected system.

<https://searchsecurity.techtarget.com/definition/antimalware>

<https://www.symantec.com/theme/star>

Quarantine/Virus Chest

- A suspicious file can be isolated in a folder or database called **quarantine**:
 - E.g., if the result of the heuristic analysis is positive and you are waiting for updates of the signatures
- The suspicious file is not deleted but made harmless: the user can decide when to remove it or eventually restore it in case of a false positive
 - Interacting with a file in quarantine is possible only through the antivirus program
- A file in quarantine is often stored encrypted to prevent its execution
- The quarantine system architecture is typically proprietary

Static vs. Dynamic Analysis

- Static Analysis
 - Check the code without execution
 - Filtering: scan with different antivirus and check if they return same result with different name
 - Weeding: remove the correct part of files as junk to better identify the virus
 - Code analysis: check binary code to understand if it is an executable
 - Disassembling: check if the byte code shows something unusual
- Dynamic Analysis
 - Check the execution of codes inside a virtual sandbox
 - Monitor
 - File changes
 - Registry changes
 - Processes and threads
 - Network ports

How to Check if AV Software is Running?

- Eicar signature:
 - X5O!P%@AP[4\PZX54(P^)7CC)7}\$EICAR-STANDARD-ANTIVIRUS-TEST-FILE!\$H+H*
- www.caro.org
- www.eicar.org

AntiVirus evaluation

- **Shield**

- Background process (service/daemon)
- Scans each time a file is touched (open, copy, execute, etc.)

- **On-demand**

- Scan on explicit user request or according to regular schedule
- On a suspicious file, directory, drive, etc.

Performance test of scan techniques

- **Comparative/Performance:** check the number of already known viruses that are found and the time to perform the scan
- **False alarm test:** number of false viruses detected
- **Heuristic / Behaviour Tests:** measure the proactive protection capabilities

Anti-viruses are ranked using both parameters: <http://www.av-comparatives.org/>

Resources

- Symantec's Internet Security Threat Report
 - Published annually
- Countdown to zero day by Kim Zetter, 2014
- Art of Computer Virus Research and Defense by Peter Szor
- <http://virus.wikidot.com/>

Responsible Disclosure

- What happens if someone discovers a vulnerability in software?
 - 2008: MBTA sued three MIT students to prevent them from giving a talk about vulnerabilities in the subway fare system
 - 2019: researcher Jonathan Leitschuh discovered a vulnerability in Zoom, which they did not fix until he publicly disclosed it
- Today, many companies have bug bounty programs in place to encourage responsible disclosure of vulnerabilities
- Disclosure deadlines: amount of time researchers give companies to patch vulnerabilities before disclosure
 - Often varies by company and by how critical the vulnerability is

SolarWinds Hack

- **What happened?**
 - Texas-based IT management company
 - hackers able to compromise networks of many other companies and deliver malware
 - supply-chain attack
 - malware inserted into update of Orion system
 - Orion: allows companies to see what is going on in their network
 - Hackers used AWS as a disguise
 - White house says at least 100 companies impacted (Microsoft included) + US government agencies
- **Response**
 - FireEye, a cybersecurity company impacted discovered the hack
 - SolarWinds issued a security advisory + what defensive measures could be taken
 - FBI Investigation to find the actors
- **Why did this happen?**
 - Bad security practices
 - “solarwinds123” used as a password for secure server (security researcher already warned SolarWinds of this!)

Underinvestment in Cybersecurity

- Why were basic security practices not followed at SolarWinds?
- “Employees say that under [CEO] Mr. Thompson ... every part of the business was examined for cost savings and **common security practices were eschewed because of their expense**. His approach helped almost triple SolarWinds’ annual profit margins to more than \$453 million in 2019 from \$152 million in 2010.”
- Bruce Schneier: “The market does not reward security, safety or transparency. It doesn't reward reliability past a bare minimum, and it doesn't reward resilience at all.”
- Core problem: limited economic incentives to invest in cybersecurity
 - Expense with diminishing returns
 - Limited legal liability
 - Small factor in customers’ decisions => small effect on share price
 - Supply chain security

Investment under ideal circumstances

- Gordon-Loeb model: even with optimal incentives, firms will never invest more than 37% of expected damage from security breaches in cybersecurity
- Caused by cybersecurity not generating profit and having diminishing returns on investment
- If you expect fire damage to cause \$10,000 damage, it doesn't make sense to purchase a \$10,000 device that reduces the probability of fire damage
- Result: total damage caused by cybersecurity will always significantly exceed investment in cybersecurity

Legal liability

- Having poor cybersecurity is legal
- Limited laws regulating cybersecurity standards
- Federal Trade Commission relies on “unfair or deceptive acts” to press charges
- Customers and shareholders need extreme cases of negligence or false statements
 - Class-action lawsuit against SolarWinds by shareholders, but only because they allege false and misleading statements
- As long as an honest effort is made, very little legal risk in having bad cybersecurity

Lack of business consequences

- Over time, customers tend to forgive and forget data breaches
- Equifax, eBay, Adobe, and Marriott all recovered from their breaches
- In corporate context, incentives in procurement favour functionality and cost over possible cybersecurity risks
- Difficult to evaluate cybersecurity between companies
- Share prices usually drop heavily after a data breach, but studies show a negligible long-term effect
- More recent data breaches have had smaller share price drops due to “breach fatigue”

Supply chain issues

- Centralization of software has created points of vulnerability that dramatically reduce hacker effort
 - SolarWinds allowed hackers to access 18,000 systems
- Vulnerabilities in one company's product have cascading effects beyond their immediate customers
 - CISA: 30% of SolarWinds victims did not use SolarWinds
- Example: 2017 NotPetya attack
 - Malware deployed by a malicious automatic update in MeDoc, Ukrainian tax preparation software
 - Caused \$10 billion damage
 - Damaged pharmaceutical production, global shipping, hospital systems

What We Have Learned

- Types of malware
- Historical evolution of malware
- Modeling malware propagation
- Concealment techniques
- Undecidability of malware detection
- Heuristic techniques for malware detection